



Common Field Devices

Notification Devices

Dome Alarm Bell

Features

- UL approved.
- High sound level output.
- Low power consumption.
- 6", 8" and 10" dome sizes.
- Quick and easy installation.
- Interchangeable base.
- Zero standby current.
- Low current consumption for efficient operation over long wire runs.
- Loud, distinctive and clear ringing sound.
- Corrosion resistant finish.
- IP 65 rated weatherproof

Product Overview

- DEMCO UL Certified Dome Alarm Bell series is designed to meet the needs of fire fighting and detection system with central control panel.
- The UL 464 listed DEMCO Alarm Bells embraced simplicity in design. They incorporate fewer working parts, easy to be installed and operate at high level of efficiency thus enable them to perform under most adverse conditions.

Decibel Ratings / Weight

Model	Size	dB @ 3m (10ft)	Gross Weight
D-122-6	6"	95 dB	700g / 1.5lb
D-122-8	8"	83 dB	1,150g / 2.5lb
D-122-10	10"	85 dB	1,600g / 3.5lb

Models

Model	Size	Type	Voltage
D-122-6	6"	Motorised	24V DC
D-122-8	8"	Motorised	24V DC
D-122-10	10"	Motorised	24V DC
D-142-6	6"	Solenoid	6V DC
D-142-12	6"	Solenoid	12V DC
D-142	6"	Solenoid	24V DC
D-142-120	6"	Solenoid	120V AC
D-142-220	6"	Solenoid	220V AC
D-142WP-6	6"	Solenoid	6V DC
D-142WP-12	6"	Solenoid	12V DC
D-142WP-	6"	Solenoid	24V DC
D-142WP-120	6"	Solenoid	120V AC
D-142WP-220	6"	Solenoid	220V AC



Weatherproof 4" Square Outlet Box

