





Foam Concentrates | SFFF¹ | Enviro USP



SPECIFICATIONS

Related documents	TDS - Fomtec Enviro USP.pdf
Approvals	 
Appearance	Clear yellowish liquid
Specific gravity @ 20 °C	1.04 +/- 0.01 g/ml
Approximate viscosity @ 20 °C	Pseudoplastic (see technical data sheet)
pH	6.5 - 8.5
Freezing point	- 11 °C
Recommended storage temperature	- 0 °C to + 55 °C
Suspended sediment (v/v)	< 0.2 %
Discharge device usage	Sprinkler, low & medium expansion
Packaging	25 l drum 200 l barrel 1,000 l IBC
Applications	Class A & B hydrocarbon fires
Features	<ul style="list-style-type: none">• Approved for use with sprinklers (FM5130 & UL162)• Fluorine free• Biodegradable
Recommended proportioning ratio	2 %, 3 % or 6 %

Note : Foam concentrate is UL Listed and FM Approved as part of a fire extinguishing system combining specific proportioning devices, bladder tanks and discharge devices. Approved system components can be found at <https://iq.ulprospector.com> or www.approvalguide.com

Part number	Volume (l)
F-ENVIRO3USP/25	25
F-ENVIRO3USP/200	200
F-ENVIRO3USP/1000	1,000

¹ SFFF = Synthetic Fluorine Free Foam

Note: This document contains basic product information only. Information, photos and drawings are not contractually binding. In all cases, the manufacturer's full technical documentation (see "Related Documents" above) remains the reference document. Note that certificates, test reports and approvals may be published in the OEM name. The contents of this publication are subject to modifications without notice. All rights reserved

Trusted above all.

Viking S.A. (ed.) | 21, Z.I. Haneboesch | L-4562 Differdange/Nieder Korn | Luxembourg | vikinglux@viking-emea.com | www.viking-emea.com

